



Product Highlights:

- Durable, metal enclosure for housing an internal drive
- Blazing-fast USB 3.2 Gen 2 interface delivers data transfer rates up to 10Gbps¹
- Integrated metal housing and heat dissipation sticker help keep your drive cool
- Portable design features a lanyard hole and a rugged bumper for added convenience and protection
- No tools required, easy installation



Turn an Internal Drive into a Portable Drive

Repurpose an internal M.2 drive as a portable device with this convenient SSD enclosure and enjoy USB 3.2 Gen 2 performance for data transfer rates up to 10Gbps¹. With its aluminum metal housing, it provides excellent heat dissipation and comes with a lanyard hole and a rugged bumper for added convenience and protection.

Repurpose your M.2 SSD. This enclosure allows you to turn an internal drive into a portable device.

Blazing-fast Performance. With its USB 3.2 Gen 2 high-speed interface, the enclosure enables data transfer rates up to 10Gbps¹.

Keeps your Drive Cool. The enclosure offers excellent heat dissipation thanks to integrated metal housing and a heat dissipation sticker.

Convenient Design. This enclosure also includes a lanyard hole and a rugged bumper for deflecting bumps and blows.

Rigorously Tested. All Lexar products undergo extensive testing in the Lexar Quality Labs, facilities with thousands of different cameras and digital devices to ensure performance, quality, compatibility, and reliability.

For more than 27 years, Lexar has been trusted as a leading global brand of memory solutions. Our award-winning lineup includes memory cards, USB flash drives, card readers, solid-state drives, and DRAM. With so many options, it's easy to find the right Lexar solution to fit your needs. Lexar products are available worldwide at major retail and e-tail stores. For more information or support, visit www.lexar.com.

Lexar Retail Sku	Region	Single UPC Code	Inner Carton UPC Code	Inner Carton Qty
LPAE300-RNBNG	Global	843367132928	60843367132920	20

Specifications

Devices	M.2 PCIe NVMe™ SSD – up to 4TB M key and B+M key – form factors 2230/2242/2260/2280
Interface	USB 3.2 Gen 2 Type-C
Operating Temperature	0°C to 40°C (32°F to 104°F)
Storage Temperature	-25°C to 85°C (-13°F to 185°F)
Dimensions (L x W x H)	115mm x 38mm x 12mm / 4.52" x 1.49" x 0.47"
Weight	67g / 0.148lbs
Warranty	Two-year limited warranty

¹Theoretical transfer speeds for the NVMe protocol are up to 10Gbps. Speeds are based on internal testing. Actual performance may vary. Lexar is not liable for any loss of data or images.

[Product page only]

Product appearance, performance, software offerings, and packaging may vary depending on ship date and available inventory. Actual usable memory capacity may vary. 1GB equals 1 billion bytes.

www.lexar.com

©2023 All Rights Reserved. Information, products, specifications, and features are subject to change without notice. Neither Lexar nor Longsys is responsible for omissions or errors in typography or photography. Lexar, the Lexar logo, and all other Lexar trademarks are the property of Longsys Electronics (HK) Co., Ltd. or Shenzhen Longsys Electronics Co., Ltd. All other trademarks are property of their respective owners.