



Make It Yours.

# Hyper H410R RGB



The Hyper H410R RGB, a new member of the longstanding Hyper Series, is an affordable, compact and high performance air cooler that its compact heatsink is a great match for small form factor system. The special fin design optimizes air flow toward heatpipes. Its 92mm squared RGB fan features a wide fan speed range and can be fine tuned for maximum airflow and cooling performance or silent operation. Compatible with all RGB certified motherboards.

## Features

**RGB LED Controller** - The wired RGB LED Controller allows for customizable colors and effects with just the touch of a button

**Outstanding Performance in Compact Size** - The Hyper H410R RGB is a small low-profile quiet cooler designed to fit in limited spaces. With its outstanding performance in its class, it is clearly a perfect solution for small form factor cases.

**Direct Contact Technology** - 4 heat pipes with Direct Contact Technology effectively provide excellent heat dissipation

**Precise Combination of Air Flow and Heat sink** - Stacked fin array ensure least airflow resistance which allows cooler air flow into the heat sink

**Snap and Play** - Intuitive fan bracket design makes upgrading and removing the fan a breeze.

## Specifications & Packing Information

EAN code	4719512094679
UPC code	884102067099
Net weight (Kg)	0.54
Gross weight (Kg)	0.66
Carton dimension (L x W x H)	60.7 x 38.5 x 22 cm
Unit/Carton	18 pcs

Product Name	Hyper H410R RGB
Product Number	RR-H410-20PC-R1
CPU socket*	Intel LGA 2066 / 2011-v3 / 2011 / 1151 / 1150 / 1155 / 1156 / 1366 AMD AM4 / AM3+ / AM3 / AM2+ / AM2 / FM2+ / FM2 / FM1
Dimensions (LxWxH)	102 x 83.4 x 136 mm ( 4 x 3.3 x 5.4 inch )
Heatsink Dimensions (LxWxH)	90 x 63.5 x 136 mm ( 3.5 x 2.5 x 5.4 inch )
Heatsink Material	4 Heatpipes /Direct Contact /Aluminum Fins
Fan Dimensions	92 x 92 x 25 mm (3.6 x 3.6 x 1 inch)
Fan Speed	600-2,000 RPM (PWM) ± 10%
Fan Air Flow	34.1 CFM (Max)
Fan Air Pressure	1.79mm H2O (Max)
MTTF	40,000 hours
LED color	RGB
Noise Level	6~29 dBA
Connector	4-Pin (PWM)
Rated Voltage	12 VDC
Rated Current	0.24 A
Safety Current	0.4 A
Power Consumption	2.88 W
Warranty	2 years

Cont.	W/ Pallet	Carton/ Pallet	W/O Pallet
20'	7128	30	N/A
40'	14256	30	N/A
40 HQ	15840	30	N/A
45 HQ	17280	30	N/A