



# PRIME PX ATX 3.0



## SPECIAL FEATURES

- ❖ ATX 3.0 and PCIe 5.0 Compatible
- ❖ Super-High Efficiency, 80 PLUS® Platinum Certified
- ❖ Cybenetics ETA Titanium and Lambda A Certified
- ❖ Fully Modular
- ❖ Top-Quality 135 mm Fluid Dynamic Bearing Fan
- ❖ Digital Hybrid Fan Control
- ❖ Micro Tolerance Load Regulation (MTLR) [0.5 %]
- ❖ Super Low Ripple Noise [under 20 mV]
- ❖ Cable-free Connection Design
- ❖ Gold Plated High Current Terminal (MB, CPU and PCIe)
- ❖ Multi-GPU Technology Support

## POWER DISTRIBUTION

Model	+3.3 V	+5 V	+12 V	-12 V	+5 Vsb	Total Power
PRIME PX-1600	25 A	25 A	133.3 A	0.5 A	3 A	1600 W
	125 W		1600 W	6 W	15 W	



For more information on Cybenetics certifications please visit: [www.cybenetics.com](http://www.cybenetics.com).

## CONNECTOR QUANTITY

Cable							
Model	Main Power (24P / 20P) 610 mm	EPS 12 V / ATX 12 V (8P / 4P) 650 mm	PCI-E (8P / 6P)	SATA	Peripheral (4P)	FDD (4P)	12V HPWR (12+4 Pins)
PRIME PX-1600	1	3	6	4	1	0	2



Safety & EMI / EMC

Protection Features: OPP / OVP / UVP / SCP / OCP / OTP

Dimensions: 210 mm (L) x 150 mm (W) x 86 mm (H)



Specifications may change without prior notice



Headquarters [sales@seasonic.com](mailto:sales@seasonic.com)

USA [ssa.sales@seasonic.com](mailto:ssa.sales@seasonic.com)

Europe [sse.sales@seasonic.com](mailto:sse.sales@seasonic.com)

[www.seasonic.com](http://www.seasonic.com)