

EVGA 650 GQ, 80+ GOLD 650W, Semi Modular, EVGA ECO Mode, 5 Year Warranty, Power Supply 210-GQ-0650-V2 (EU)

Part Number: 210-GQ-0650-V2



Ready for 4th Generation Intel Core Processors (C6/C7 Idle Mode)

Introducing the latest in the EVGA power supply lineup; the GQ series. These power supplies take some of the best features from EVGA�s award winning power supplies, like EVGA ECO fan mode for near silent operation, Japanese Capacitor Design and a highly efficient design, at an excellent value. These new power supplies are 80 Plus Gold rated and offer an outstanding 5 Year Warranty that�s backed by world class EVGA support.

FEATURES

- 100% Japanese Capacitors ensure long-term reliability
- 5 Year Warranty and unparalleled EVGA Customer Support
- 80 PLUS Gold certified, with 90% (115VAC) / 92% (220VAC~240VAC) efficiency or higher under typical loads
- Active Clamp +DC to DC design for efficient operation
- Active Power Factor Correction
- EVGA ECO Intelligent Thermal Control System eliminates fan noise at low to medium loads
- Modular Design to reduce clutter and improve airflow
- NVIDIA SLI & AMD Crossfire Ready
- Whisper Silent with 135mm Fluid Dynamic Bearing Fan

CABLE LENGTH

| ATX Cable | 1x 600mm (m) | | |
|---------------------------|----------------------------|--|--|
| EPS Cable | 2x 650mm (m) | | |
| PCIe Cable | 2x 650mm, 750mm (m) | | |
| SATA Cable | 3x 550mm, 650mm, 750mm (m) | | |
| Four-Pin Peripheral Cable | 1x 550mm, 650mm, 750mm (m) | | |
| Floppy Adapter | 1x 100mm (m) | | |
| AC Power | 1x 1530mm (m) | | |
| Modular Cable Type | Semi-Modular | | |

CONNECTOR QUANTITY

| 24 Pin ATX | 1x | | |
|---------------------|---------------|--|--|
| EPS (CPU) | 2x 8pin (4+4) | | |
| PCle | 4x 8pin (6+2) | | |
| SATA | 9x | | |
| Four-Pin Peripheral | 3x | | |
| Floppy | 2x | | |

INPUT

| Input Voltage | 100 - 240 VAC | | |
|-----------------------|--|--|--|
| AC Input | 10A | | |
| Input Frequency Range | 50 - 60 Hz | | |
| Efficiency | 90% (115VAC) / 92% (220VAC~240VAC) or Higher Typical | | |

OUTPUT

| Rail | +3.3V | +5V | +12V | -12V | +5Vsb |
|----------------|-------------|------|------|------|-------|
| Max output 24A | 24A | 24A | 54A | 0.5A | 3A |
| | | | 648W | | |
| | 120W | 120W | | 6W | 15W |
| Total | 650W @ +50C | | | | |

ADDITIONAL DETAILS

| Operating Temperature | 0° to 50° C | | |
|-----------------------|---|--|--|
| Japanese Capacitors | 100% | | |
| ECO Mode | Yes | | |
| MTBF | 100,000 Hours | | |
| Gross Weight | 5.50 lbs | | |
| Size | 85mm (H) x 150mm (W) x 165mm (L) | | |
| Approvals | TUV, CB, CE, FCC, RCM, cTUVus, WEEE, RoHS Compliance with ErP Lot 6 2013 Requirement | | |
| Fan Size / Bearing | 135mm Fluid Dynamic Bearing | | |
| UPC | 843368035723 | | |
| EAN | 4250812409195 | | |

PRODUCT WARRANTY

